










Fire door EI₂30-(C)

Flush and glazed entrance doors with the same look as the rest of our assortment



 Burn-through time: 39 minutes	 Burglar-proof: RC2-approved	 Weight: Approx. 35 kg/m ²
 Noise reduction: Approx. 35 dB Rw+Ctr	 U-value for the entire door: 0,9-1,0 W/m ² K	 Types of wood: Pine wood or any other heavier sort of wood
 Materials: Wood & wood/aluminium	 Max. size: 1200x2450	 Classification: From the outside: EI30 From the inside: EI60

// ELEGANT DESIGN

The fire doors have the same look and design as our other façade doors and windows.

// OPTIONAL TYPE OF WOOD

The doors are supplied in a type of wood of your own personal choosing. However, the only requirement is that the preferred wood species is heavier than pine wood.

// ASSEMBLED ELEMENTS

The fire doors can be delivered as a complete entrance area, in which the doors are built together with our fire windows to one unit.

// PROFESSIONAL CALCULATION

We should be happy to make our expertise available to you and help you find the optimal solution in accordance with current legislation.

// EASY MAINTENANCE

The outer aluminium part ensures a long life and minimal maintenance.

// NOISE REDUCTION

Excellent noise-reducing properties ensure peace and quiet indoors even if the nearest neighbour is a very busy road.

// GREAT FLEXIBILITY

The flush entrance door can be ordered with glazing bars with or without profiles in varying width.

// BR 2018

Our production facilities have been certified according to EN 16034 and comply with the new requirements of the building regulations effective as at 1st November 2019.

// TESTED AND APPROVED SOLUTIONS

The fire doors meet the strictest requirements and have been tested at The Danish Institute of Fire and Security Technology.



Fire door EI₂30-(C)

Reference pictures

